Workmaster

SUPER DUTY ROLLING METAL LADDER

For the workspace that demands the toughest ladder, Cotterman introduces the Super Duty Workmaster ladder.



STATE

Division of Material Control, Inc. P.O. Box 168 130 Seltzer Rd. Croswell, MI 48422 810-679-4400 • FAX 810-679-4510 TOLL FREE 800-5-LADDER 8 A.M. – 5 P.M. MON. THRU FRI. (EASTERN STANDARD TIME) www.cotterman.com

R

Distributed by:



Toll-Free: 1-800-833-0800 WWW.INDUSTRIALLADDER.COM

Cotternali Workmaster

Every day work is done where equipment needs to be able to take a beating and keep working. For the toughest jobs, Cotterman introduces the Super Duty Workmaster ladder. Built with extra heavy duty components, this ladder is resistant to all the dings and bumps in harsh work environments.

The Workmaster is also customizable with an array of features and options to adapt the ladder to specific work areas.

Essentially the Workmaster Super Duty Ladder can become a mobile assembly or repair shop for anything out of reach.

Two tone powder coat finish creates high visibility and can be order in an array of different colors.

For the toughest work areas, step up to the Cotterman Workmaster Super Duty.



MODULAR FRONT LEG AND SAFELOCK FIELD REPLACEABLE, ADJUSTABLE FRONT LEGS LEVEL THE LADDER



OPTIONAL UTILITY TRAY 150 Ib. CAPACITY

1.5" TUBE HANDRAILS POWDER COATED

HEAVY DUTY CASTERS, CURVED BASE AND BACK PANEL AND BOLT LOCATION FOR EASY ASSEMBLY

OPTIONAL TOOL PEGBOARD



STANDARD BACK TOOL BOARD

> OPTIONAL TOOL BOX

SUPERIOR CONSTRUCTION

- 1000 pound capacity allows for tool cabinet and/or tool pegboard
- 1 1/2" diameter x 14 gauge tube construction
- 7" x 10 gauge Stair Stringer
- Contoured back and base panel assembly to allow unobstructed access to equipment and reduce possibility of impact damage
- 1 ½" x 14 gauge steel tube base and back panel, bolt on for ease of replacement

PLATFORM WITH OPTIONAL SELF-CLOSING GATES, FULLY ENCLOSE PERSONNEL. TOEBOARDS AND 42" GUARDRAILS STANDARD

24" x 24"

Contra la

OPTIONAL FRONT SELF-CLOSING GATE

> OPTIONAL REAR SELF-CLOSING GATE



SPECIFICATIONS & DIMENSIONS

			Platform	Overall	Step Width	Base Width	Base Length	Load Capacity	Wt
Mfr. Model No.	Steps	Tread Type	Height	Height	(In)	(In)	(In)	(lbs)	(lbs)
WMX05R37A3P3	5	Grip Strut	4' 2"	7' 8"	24	37	56	1,000	297
WMX06R37A3P3	6	Grip Strut	5'	8' 6"	24	37	62	1,000	314
WMX07R37A3P3	7	Grip Strut	5' 10"	9' 4"	24	37	68	1,000	343
WMX08R37A3P3	8	Grip Strut	6' 8"	10' 2"	24	37	74	1,000	360
WMX09R37A3P3	9	Grip Strut	7' 6"	11'	24	37	80	1,000	380
WMX10R37A3P3	10	Grip Strut	8' 4"	11' 10"	24	37	86	1,000	397
WMX11R42A3P3	11	Grip Strut	9' 2"	12' 8"	24	42	92	1,000	423
WMX12R42A3P3	12	Grip Strut	10'	13' 6"	24	42	98	1,000	440
WMX05R37A9P3	5	Open Grip	4' 2"	7' 8"	24	37	56	1,000	301
WMX06R37A9P3	6	Open Grip	5'	8' 6"	24	37	62	1,000	318
WMX07R37A9P3	7	Open Grip	5' 10"	9' 4"	24	37	68	1,000	347
WMX08R37A9P3	8	Open Grip	6' 8"	10' 2"	24	37	74	1,000	364
WMX09R37A9P3	9	Open Grip	7' 6"	11'	24	37	80	1,000	384
WMX10R37A9P3	10	Open Grip	8' 4"	11' 10"	24	37	86	1,000	401
WMX11R42A9P3	11	Open Grip	9' 2"	12' 8"	24	42	92	1,000	427
WMX12R42A9P3	12	Open Grip	10'	13' 6"	24	42	98	1,000	444

AVAILABLE OPTIONS

- Platform safety gate (factory or field installed) available for all 4 sides of platform
- Accessory platform can accommodate numerous options including: Tool cabinet, Peg board panel, Bin/shelving unit, 24" x 24" Utility tray with 150 lb. capacity





www.cotterman.com · info@cotterman.com