

Distributed by:



Toll-Free: 1-800-833-0800 www.IndustrialLadder.com



- · Built with high strength polyethylene film encased with premium scrim yarns.
- · Blue reinforced eyelets bands are highly resistant and prepunched every 4" (10 cm).
- TUFTARP is designed to be installed from inside the scaffold by piercing the bungee tie into the eyelet holes. Simply fasten the toggle end of the tie to the scaffold tube.
- · TUFTARP is made of flame retardant material.
- · Meets OSHA requirements.



	SCAFFOLD TARP	
DIMENSIONS	13 X 100 FT (1,300 SQ. FT.) 4 X 30.5 M (122 M²)	
MATERIAL	FLAME RETARDANT POLYETHYLENE	
WEIGHT	69 LB (7.37 OZ/SQ.YD.) 31.1 KG (250 G/M ²)	
MODEL	M-MTE13100	
UPC	778300000586	

1		
		BUNGEE TIE
	DIMENSIONS	11 IN.
	MODEL	M-MBT11
		SCREW CONNECTOR
	DIMENSIONS	1.25 IN. DIAM.
	MODEL	M-MTESCREW

INSTALLATION

Blue reinforced eyelets bands are highly resistant and prepunched every 4" (10 cm). Designed to be installed from inside.











WWW.TUFTARP.COM

1 800 363-7587