6300SERIES Stepladder

Model No.	Size	Approx. Width	Approx. Spread	Approx. Cu. Ft. Per Unit	Approx. Shipping Wt. Lbs.	Load Capacity Lbs.
6303	3'	18-1/8"	23-1/8"	2.0	13.0	375
6304	4'	19-7/8"	29"	3.0	16.0	375
6305	5'	21-5/8"	35-1/4"	4.1	19.0	375
6306	6'	23-3/8"	41-1/4"	5.3	22.0	375
6308	8'	26-7/8"	53-5/8"	8.1	30.0	375
6210	10'	30-3/8"	65-7/8"	12.5	39.0	375
6212	12'	33-7/8"	78-1/4"	15.0	48.0	375

5-3/4" x 13" Front Rails: 3-1/8" wide Front Flange: 1-3/16" wide 3" wide Rear Rails: 1-7/8" wide Rear Flange: 1-3/16" wide

T6300SERIES Twin Stepladder

Model No.	Size	Approx. Width	Approx. Spread	Approx. Cu. Ft. Per Unit	Approx. Shipping Wt. Lbs.	Load Capacity Lbs.
T6304	4'	19-7/8"	36-1/8"	4.6	19.0	300
T6306	6'	23-3/8"	50-1/8"	8.0	27.0	300
T6308	8'	26-7/8"	64-1/8"	12.3	37.0	300
T6210	10'	30-3/8"	78-1/8"	17.3	54.5	300
T6212	12'	33-7/8"	92-1/8"	23.2	68.5	300

8-1/2" x 13" 3-1/8" wide 1-3/16" wide 3" wide

D6300-2SERIES Extension Ladder

Model No.	Total Length Sections	Max. Working Length	Approx. Cu. Ft. Per Unit	Approx. Shipping Wt. Lbs.	Load Capacity Lbs.
D6316-2	16'	13'	7.0	36.5	300
D6320-2	20'	17'	8.7	44.5	300
D6324-2	24'	21'	10.3	52.0	300
D6328-2	28'	25'	12.0	59.5	300
D6332-2	32'	29'	13.7	71.5	300
D6336-2	36'	32'	15.3	80.5	300
D6340-2	40'	35'	17.0	88.5	300

3-1/8" wide 1-3/16" wide Flange: 1-1/2" wide 16" outside rails Base Width: 19" outside shoes







Werner Co. 93 Werner Rd. Greenville, PA 16125-9499 Phone: 888-523-3371 Fax: 888-456-8458 www.wernerco.com



Werner 6300 Ladder Family

This line of feature-rich, non-conductive fiberglass ladders was designed for the professional user. The single-sided stepladder has a 375 pound (Type IAA) load capacity and the double-sided stepladder and extension ladder (16' to 32') are rated for 300 pounds (Type IA). There's a 6300 perfect for any professional's ladder requirements!



ToolLasso



JobBucket



Cut-in Pail

6300SERIES Stepladder





Ladders designed for the professional.

T6300SERIES Twin Stepladder

★★★ PER SIDE

Plated steel spreaders positioned inside

increased resistance

ladder rails for

to damage.

Type IA Duty Rating









Type IA Duty Rating



Heavy duty aluminum pulley with 5/16" polypropylene rope.

> Direct rung to rail connections.
> Twist-Proof® due to the exclusive

Includes pre-pierced holes at top of fly for field installation of accessories. Slip-resistant Traction-Tred® D-rungs ALFLO® rung joints. Rugged gravity spring locks operate smoothly Shoe is slotted, allowing entire weight of ladder to rest on shoe pad.

Available in 16', 20', 24', 28', 32', 36' and 40' heights

Ideal for 2 people (1 person each side only).

Molded external rail

shields help protect

against abrasion damage.

NOTE: When used as a double stepladder, the maximum load per side, including person and materials, shall not exceed the duty rating of the ladder

and foot pad combination

provides enhanced bracing strength and increased

protection against damage

Available in 4', 6', 8', 10' and 12' heights

protection against damage.