

WERNER®





- Easy to use Adjusts in 3/8" increments up to 8-1/4"
- Convenient Built-in bubble level
- **Dual action foot**For use on hard or penetrable surfaces

- Lightweight aluminum
- Exclusive ALFLO® Twist-Proof® performance
- Slip-resistant steps and rugged locks



D1700-2EQ Series



Includes User and Materials

Type II Duty Rating

SPECIFICATIONS D1700-2EQ Series

	Total	Maximum	Approx.	Approx.
Model	Length	Working	Cu. Ft.	Shipping
No.	Sections	Length	Per Unit	Wt. Lbs.
D1716-2EQ‡	16'	13'	6.51	27.5
D1720-2EQ	20'	17'	8.08	32.5
D1724-2EQ	24'	21'	9.64	39
D1728-2EQ	28'	25'	11.21	48.5

‡ Note: D1716-2EQ is not equipped with rope and pulley

DIMENSIONS

Rails:	3" wide	Fly Width: 14-1/4" outside rails
Flange:	1-1/16" wide	Base Width: 17-3/8" outside rails
Rungs:	1-3/4"	(20-3/4" to outside of feet)

EQUALIZER ALUMINUM EXTENSION LADDER WITH INTEGRATED LEVELER

D1800-2EQ Series



Includes User and Materials

Type I Duty Rating

SPECIFICATIONS D1800-2EQ Series

	Total	Maximum	Approx.	Approx.
Model	Length	Working	Cu. Ft.	Shipping
No.	Sections	Length	Per Unit	Wt. Lbs.
D1816-2EQ‡	16'	13'	6.51	31.5
D1820-2EQ	20'	17'	8.08	37.5
D1824-2EQ	24'	21'	9.64	45.5
D1828-2EQ	28'	25'	11.21	56

‡ Note: D1816-2EQ is not equipped with rope and pulley

DIMENSIONS

Rails:	3" wide	Fly Width: 14-1/4" outside rails
Flange:	1-1/16" wide	Base Width: 17-3/8" outside rails
Rungs:	1-3/4"	(20-3/4" to outside of feet)

