

6' Steel Rolling Scaffold

Easy one-person assembly

No tools required for quick setup and tear down



SRS-72 - 6' Steel Rolling Scaffold

LOAD CAPACITY
1000 lbs.

Includes User and Materials



Sections stack easily



Protected locking pins prevent accidental release



Deck pin secures plywood to frame



Swivel locking casters



wernerladder.com



6' Steel Rolling Scaffold

- 1000 lbs. distributed load capacity
- Easy one-person assembly
- No tools required for quick setup and tear down
- Stackable frames (2 high maximum)
- All ball bearing casters remove easily for stacking

- Simple platform adjustment
- Platform height can be adjusted in 2" increments for unique working heights and uneven surfaces
- Compatible and interchangeable with leading competitor



SPECIFICATIONS SRS-72

Model No.	Description	Approx. Width	Approx. Length	Approx. Height	Approx. Shipping Weight
SRS-72	Steel Rolling Scaffold	29-1/2"	73-3/4"	74-7/8"	143.5 lbs.

Includes:

Qty.	Description	Approx. Width	Approx. Length	Approx. Height
2	End Frames	29"	68-3/4"	1-1/2"
2	Side Braces	1-1/2"	73-7/8"	17-7/8"
1	Plywood Deck	28-1/2"	66-3/4"	2"
4	Locking Casters	5-1/8"	1-1/8"	9-7/8"

ACCESSORIES (available separately)

Model No.	Description	Approx. Width (ea.)	Approx. Length (ea.)	Approx. Height (ea.)	Approx. Shipping Weight (carton)
SRO-72-4	Outrigger (4-pc master carton)	18"	20-3/4"	---	37.5 lbs.
SRG-72	Guard Rail & Toeboard System	28-7/8"	69-5/8"	42"	70.5 lbs.
SRC-72-4	5" Casters (4-pc master carton)	5-1/8"	1-1/8"	9-7/8"	20.0 lbs.
SRD-72	Plywood Deck	28-1/2"	66-3/4"	2"	32.5 lbs.

Note: Guard rail and outriggers required when stacking two units regardless of height.

SRS-72 - 6' Steel Rolling Scaffold

1000 LOAD CAPACITY **lbs.**

Includes User and Materials