




H91400X

Arc Flash Full Body Harness

FEATURES

- Meets requirements of ASTM F887
- 1¾ inch Kevlar® Webbing
- Dielectric Hardware
- SIGMA™ flame resistant (FR) Backpad and protective label cover
- Built in Relief Straps assist user to reach a gravity override seated position after a fall arrest



SPECIFICATIONS

Model No.	Size	D-Rings	D-Ring Material	Chest Connection	Leg Connection	Capacity	Approx. Weight	Compliance Standards
H914001	Small	Back	Dielectric	Pass-Thru	Pass-Thru	400 lbs (181 kg)	3.9 lbs (1.8 kg)	ANSI Z359.11 OSHA 29 CFR 1910 & 1926
H914002	Medium/Large	Back	Dielectric	Pass-Thru	Pass-Thru	400 lbs (181 kg)	4.0 lbs (1.8 kg)	ANSI Z359.11 OSHA 29 CFR 1910 & 1926
H914004	X-Large	Back	Dielectric	Pass-Thru	Pass-Thru	400 lbs (181 kg)	4.0 lbs (1.8 kg)	ANSI Z359.11 OSHA 29 CFR 1910 & 1926
H914005	XX-Large	Back	Dielectric	Pass-Thru	Pass-Thru	400 lbs (181 kg)	4.2 lbs (1.9 kg)	ANSI Z359.11 OSHA 29 CFR 1910 & 1926

⚠ WARNING: Compliant fall protection equipment must only be used as it was designed. Users MUST read and understand all user instructions provided with the product. Before using a fall arrest system, users must be trained in the safe use of the system, as required by OSHA 29 CFR 1910.30 and 1926.503, or local safety regulations. Misuse or failure to follow these warnings and instructions may result in injury or even death.

WORK SAFE! WORK SMART!

Technical Data Sheet